

N-Channel Super-junction MOSFET Gen I

MOSFET

Metal Oixde Semiconductor Field Effect Transistor

650V Super-junction Gen I



650V Super-junction Gen I Power Transistor

HRM65R105Fx Data Sheet

Rev. 2020 V2.0



650V Super-junction Power MOSFET Gen I

<p>Description</p> <p>650V Super-junction MOSFET Gen I</p> <p>Super-junction MOSFET Gen I is designed by HR-Micro Semiconductor Company, according to the SJ principle. This device provides an excellent Gate charge and $R_{DS(on)}$, which leads to extremely low commutation and conduction losses. So it is very suitable for AC/DC power conversion, Laptop adapter, Lighting, and industrial power applications.</p>		
<p>Features</p> <ul style="list-style-type: none"> ● Very low FOM $R_{DS(on)} \times Q_g$ ● 100% avalanche tested ● Easy to use/drive ● Ultra-fast body diode ● RoHS compliant 		
<p>Applications</p> <ul style="list-style-type: none"> ● Switch Mode Power Supply (SMPS) ● Uninterruptible Power Supply (UPS) ● Suitable for hard and soft switching (PFC and high performance LLC) ● Telecom and Solar inverter 		
<p>Key Performance Parameters</p>		
<p>Parameter</p>	<p>Value</p>	<p>Unit</p>
<p>$V_{DS} @ T_{j,max}$</p>	<p>700</p>	<p>V</p>
<p>$R_{DS(on),max}$</p>	<p>0.105</p>	<p>Ω</p>
<p>$Q_{g,typ}$</p>	<p>64.5</p>	<p>nC</p>
<p>I_D</p>	<p>40</p>	<p>A</p>
<p>$I_{D,pulse}$</p>	<p>120</p>	<p>A</p>
<p>$E_{OSS} @ 400V$</p>	<p>7.98</p>	<p>μJ</p>
<p>Body Diode di_T/dt</p>	<p>900</p>	<p>A/μs</p>
<p>Device Marking and Package Information</p>		
<p>Device</p>	<p>Package</p>	<p>Marking</p>
<p>HRM65R105FB</p>	<p>TO-263</p>	<p>65R105FB</p>
<p>HRM65R105FF</p>	<p>TO-220F</p>	<p>65R105FF</p>
<p>HRM65R105FL</p>	<p>TO-262</p>	<p>65R105FL</p>
<p>HRM65R105FP</p>	<p>TO-220</p>	<p>65R105FP</p>
<p>HRM65R105FW</p>	<p>TO-247</p>	<p>65R105FW</p>

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted			
Parameter	Symbol	Value	Unit
Drain-Source voltage($V_{GS}=0\text{V}$)	V_{DS}	650	V
Continuous Drain Current ¹⁾	I_D	$T_C = 25^\circ\text{C}$	40
		$T_C = 100^\circ\text{C}$	24
Pulsed Drain Current ²⁾	$I_{D,pulse}$	120	A
Gate-Source Voltage	V_{GS}	$\pm 30\text{V}$	V
Single Pulse Avalanche Energy	E_{AS}	796	mJ
Repetitive Avalanche Energy	E_{AR}	1.2	mJ
Avalanche Current	I_{AR}	6.6	A
MOSFET dv/dt Ruggedness, $V_{DS} = 0 \dots 480\text{V}$	dv/dt	50	V/ns
Power Dissipation For TO-263、TO-262、TO-220、TO-247	P_D	278	W
Power Dissipation For TO-220F		35	
Continuous Diode Forward Current	I_S	40	A
Diode Pulsed Current ²⁾	$I_{S,pulse}$	120	
Reverse Diode dv/dt ³⁾	dv/dt	50	V/ns
Maximum Diode Commutation Speed	di/dt	900	A/ μs
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^\circ\text{C}$

Thermal Resistance For TO-263、TO-262、TO-220、TO-247			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	R_{thJC}	0.45	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient	R_{thJA}	62	

Thermal Resistance For TO-220F			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	R_{thJC}	3.6	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient	R_{thJA}	80	

Notes

- 1) Limited by maximum junction temperature.
- 2) Repetitive Rating: Pulse width limited by maximum junction temperature.
- 3) Identical low side and high side switch with identical R_G .

Electrical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted						
Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	650	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 650V$ $V_{GS} = 0V, T_J = 25^\circ\text{C}$	--	--	4	μA
		$V_{DS} = 650V$, $V_{GS} = 0V, T_J = 150^\circ\text{C}$	--	--	4000	
Gate-Source Leakage Current	I_{GSS}	$V_{GS} = \pm 30V$	--	--	± 100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	3.0	4.0	5.0	V
Drain-Source On-State-Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 20A$	--	0.092	0.105	Ω
Gate Resistance	R_G	$f = 1.0\text{MHz}$ open drain	--	3	--	Ω
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{GS} = 0V$, $V_{DS} = 100V$ $f = 1.0\text{MHz}$	--	2940	--	μF
Output Capacitance	C_{oss}		--	102	--	
Reverse Transfer Capacitance	C_{rss}		--	3.5	--	
Total Gate Charge	Q_g	$V_{DD} = 520V, I_D = 40A$ $V_{GS} = 10V$	--	64.5	--	nC
Gate-Source Charge	Q_{gs}		--	20.0	--	
Gate-Drain Charge	Q_{gd}		--	25.4	--	
Gate Plateau Voltage	$V_{Plateau}$		--	6.6	--	V
Turn-on Delay Time	$t_{d(on)}$	$V_{DD} = 400V, I_D = 40A$ $R_G = 15\Omega, V_{GS} = 10V$	--	20	--	ns
Turn-on Rise Time	t_r		--	15	--	
Turn-off Delay Time	$t_{d(off)}$		--	70	--	
Turn-off Fall Time	t_f		--	8	--	
Drain-Source Body Diode Characteristics						
Body Diode Forward Voltage	V_{SD}	$T_J = 25^\circ\text{C}, I_{SD} = 20A$, $V_{GS} = 0V$	--	1.0	1.5	V
Reverse Recovery Time	t_{rr}	$V_R = 400V$ $I_F = 20A, di_F/dt = 100A/\mu s$	--	165	--	ns
Reverse Recovery Charge	Q_{rr}		--	1.2	--	μC
Peak Reverse Recovery Current	I_{rrm}		--	14	--	A

Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Transient Thermal Impedance For TO-263/262/220/247




Figure 2. Transient Thermal Impedance For TO-220F




Figure 3. Safe Operation Area For TO-263/262/220/247




Figure 4. Safe Operation Area For TO-220F




Figure 5. Output Characteristics





Figure 6. Transfer Characteristics



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. On-Resistance vs. Drain Current




Figure 8. Capacitance




Figure 9. Gate Charge




Figure 10. Body Diode Forward Voltage




Figure 11. Typ. Coss Stored Energy





Figure 12. On-Resistance vs. Temperature



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 13. Breakdown Voltage vs. Junction Temperature




Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform






Figure C: Unclamped Inductive Switching Test Circuit and Waveform



TO-263




Unit:mm			
Symbol	Min.	Nom	Max.
A	4.40	4.50	4.60
A1	0	0.10	0.25
A2	2.20	2.40	2.60
b	0.76	---	0.89
b1	0.75	0.80	0.85
b2	1.23	---	1.37
b3	1.22	1.27	1.32
c	0.47	---	0.60
c1	0.46	0.51	0.56
c2	1.25	1.30	1.35
D	9.10	9.20	9.30

Unit:mm			
Symbol	Min.	Nom	Max.
D1	8.00	---	---
E	9.80	9.90	10.00
E1	7.80	---	---
e	2.54 BSC		
H	14.90	15.30	15.70
L	2.00	2.30	2.60
L1	1.17	1.27	1.40
L2	---	---	1.75
L3	0.25 BSC		
L4	4.60 REF		
θ	0°	---	8°
θ_1	1°	3°	5°

Ordering information For TO-263

Package	Units/Tape	Tapes/ Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO-263	800	1	800	10	8000

TO-220F




Unit:mm			
Symbol	Min.	Nom	Max.
A	4.50	4.70	4.83
A1	2.34	2.54	2.74
A2	0.70 REF		
A3	2.56	2.76	2.93
b	0.70	---	0.90
b1	1.18	---	1.38
b2	---	---	1.47
c	0.45	0.50	0.60
D	15.67	15.87	16.07
D1	15.55	15.75	15.95

Unit:mm			
Symbol	Min.	Nom	Max.
D2	9.60	9.80	10.0
E	9.96	10.16	10.36
e	2.54 BSC		
H1	6.48	6.68	6.88
L	12.68	12.98	13.28
L1	---	---	3.50
L2	6.50 REF		
ϕP	3.08	3.18	3.28
Q	3.20	---	3.40
θ	1°	3°	5°

Ordering information For TO-220F

Package	Units/Tube	Tubes/ Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO-220F	50	40	2000	4	8000

TO-262




Unit:mm			
Symbol	Min.	Nom	Max.
A	4.40	4.50	4.60
A1	2.20	2.40	2.60
b	0.76	---	0.89
b1	0.75	0.80	0.85
b2	1.23	---	1.37
b3	1.22	1.27	1.32
c	0.47	---	0.60
c1	0.46	0.51	0.56
c2	1.25	1.30	1.35
D	9.10	9.20	9.30

Unit:mm			
Symbol	Min.	Nom	Max.
D1	8.00	---	---
E	9.80	9.90	10.00
E1	7.80	---	---
e	2.54 BSC		
L	12.90	13.20	13.50
L1	2.80	3.00	3.20
L2	1.17	1.27	1.40
L3	4.60 REF		
W	13.25	---	14.00
θ	1°	3°	5°

Ordering information For TO-262

Package	Units/Tube	Tubes/ Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO-262	50	40	2000	4	8000

TO-220




Unit:mm			
Symbol	Min.	Nom	Max.
A	4.40	4.50	4.60
A1	1.27	1.30	1.33
A2	2.30	2.40	2.50
b	0.70	---	0.90
b2	1.27	---	1.40
c	0.45	0.50	0.60
D	15.30	15.70	16.10
D1	9.10	9.20	9.30
D2	13.10	---	13.70
E	9.70	9.90	10.20

Unit:mm			
Symbol	Min.	Nom	Max.
E1	7.80	8.00	8.20
e	2.54 BSC		
e1	5.08 BSC		
H1	6.30	6.50	6.70
L	12.78	13.08	13.38
L1	---	---	3.50
L2	4.60 REF		
ΦP	3.55	3.60	3.65
Q	2.73	---	2.87
θ1	1°	3°	5°

Ordering information For TO-220

Package	Units/Tube	Tubes/ Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO-220	50	40	2000	4	8000

TO-247



Unit:mm			
Symbol	Min.	Nom	Max.
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
a	0	---	0.15
a'	0	---	0.15
b	1.16	---	1.26
b1	1.15	1.2	1.22
b2	1.96	---	2.06
b3	1.95	2.00	2.02
b4	2.96	---	3.06
b5	2.96	3.00	3.02
b6	---	---	2.25
b7	---	---	3.25
c	0.59	---	0.66
c1	0.58	0.60	0.62
D	20.90	21.00	21.10
D1	16.25	16.55	16.85

Unit:mm			
Symbol	Min.	Nom.	Max.
D2	1.05	1.17	1.35
E	15.70	15.80	15.90
E1	13.10	13.30	13.50
E2	4.40	4.50	4.60
E3	2.40	2.50	2.60
e	5.436 BSC		
L	19.80	19.92	20.10
L1	---	---	4.30
M	0.35	---	0.95
P	3.40	3.50	3.60
P1	7.00	---	7.40
P2	2.40	2.50	2.60
Q	5.60	---	6.00
S	6.05	6.15	6.25
T	9.80	---	10.20
U	6.00	---	6.40

Ordering information For TO-247

Package	Units/Tube	Tubes/ Inner Box	Units/Inner Box	Inner Box/Carton Box	Units/Carton Box
TO-247	30	20	600	5	3000

Disclaimer

HRM has made reasonable commercial efforts to ensure that the information given in this datasheet is correct. However, it must clearly be understood that such information is for guidance only and does not constitute any representation or form part of any offer or contract.

For documents and material available from this datasheet, HRM does not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, product, technology or process disclosed hereunder.

HRM reserves the rights to at its own discretion to make any changes or improvements to this datasheet. Unless said datasheet is incorporated into the formal contract, any customer should not rely on the information as any specification or product parameters duly committed by HRM. Customers are hereby advised to verify that the information contained herein is current and complete before the entering of any contract or acknowledgement of any purchase order. Accordingly, all products specified hereunder shall be sold subject to HRM's terms and conditions supplied at the time of order acknowledgement. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

HRM does not warrant or convey any license either expressed or implied under its patent rights, nor the rights of others. Reproduction of information contained herein shall be only permissible if such reproduction is without any modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. HRM is not responsible or liable for such altered documentation.

Resale of HRM's products with statements different from or beyond the parameters stated by HRM for that product or service voids all express or implied warranties for the associated HRM's product or service and is unfair and deceptive business practice. HRM is not responsible or liable for any such statements.

HRM's products are not authorized for use as critical components in life support devices or systems without the express written approval of HRM. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.